



SGD200II/SGDP240

INTEGRATED/STANDALONE CUSTOMER DISPLAY

Flat and discreet



SAGA 

FLAT AND SWIVELLING 2-LINE DISPLAY UNIT

The SAGA range of 2-line displays stands out with its two references, the SGDP240 stand-mounted version (VFD technology) and the SGD200II version integrated into the back of OVA II POS terminals (LCD technology).

The display units are available in a basic black colour, and have a completely flat screen, to match the rimless touchscreen versions of today's POS terminals.

Both display units are swivel mounted, have 2 lines of 20 characters and are USB-connected. They are ideal for displaying price, reference and quantity information for the products at the checkout.



PRODUCT KEY FEATURES

- USB connection - Windows 11 support
- Adjustable head
- Compatible with all POS set-ups
- Available as an integrated or separate version of the checkout system

DISPLAY UNIT

SPECIFICATIONS

Display technology	SGDP240: blue-green vacuum fluorescent display (VFD) SGD200II: Blue liquid crystal display (LCD)
Number of characters	40 (2 lines x 20 characters)
Interface	USB 2.0
Luminance	300 cd/m ²
Angle of vision	60°
Characters available	95 numbers/letters 32 international characters
Protocol	ESC/POS, UIMIMATE, LD220, EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL compatible
Power supply	USB- A - 5 Volts self-powered, Internal wired connector (SGD200II)
Energy consumption:	approx. 2A



SGD200II - LCD VERSION

ENVIRONMENT

Temperature in operation	+5°C/+50°C
Storage temperature	-10 / +55°C
Screen dimensions	SGDP240: 168 (L) x 66.5 (H) x 28 (D) mm SGD200II: 172 (L) x 53 (H) x 17 (D) mm
Dimensions of SGDP240 stand	169.5 (L) x 98.5 (H) x 38 (H) mm
SGDP240 tube dimensions	106.5 (L) mm x 34 mm (diameter)
SGDP240 head rotation	355°
MTBF	30,000 hours
Weight	SGDP240: Approximately 800g SGD200II: approx. 200g



Flash this code to check out the latest news on PERIMATIC