



SGPR-200II

Robust, elegant...
Our best-seller



Fast, functional receipt printer.

With its features, compact size and elegant design, the **SGPR-200II** is a customer receipt printer with all the resources required for a POS printer.

This 80 mm thermal printer is inexpensive and offers a print speed of 260 mm/sec. It has a triple USB/serial/Ethernet interface and communicates in ESC/POS and OPOS. It prints the most complex codes, such as PDF and DATAMATRIX codes.

Paper is loaded from the top of the printer. The SAGA SGPR-200II fast and robust printer will win you over with its product quality and low price.



PRODUCT KEY FEATURES

- Max. printing speed 260 mm/s
- Triple Interface: USB, RS-232, Ethernet, also comes in Bluetooth
- Can print 2D codes
- Design and configuration compatible with all major brands of POS equipment
- Receipt printing beep function available

PRINTER SPECIFICATIONS

Printing method	Direct thermal printing
Printing speed	260 mm / sec
Printing width	Max 72 mm / 512 points per line
Characters/line	Font A: 12x24 dots Font B: 9x17 dots
Points	203 DPI
Buffer	1024KB
Cutter	Total or partial cutting
Paper loading	From the top of the printer
Beep function	Available after cut
Manufacturer warranty	3 years



PAPER SPECIFICATIONS

Reference	PT80
Width	80 mm - 79.50 mm +/- 0.5 mm
Thickness	0.06~0.08 mm
Roll diameter	Max. 83 mm

PRINTABLE CHARACTERS

Fonts	PC850/PC347/PC860/PC863/PC865
Barcodes	UCP-A/UCP-E / EAN13/EAN8 / CODABAR / ITF-25 / CODE 39/ CODE 93/CODE 128
2D barcodes	QR Code, DATAMATRIX
Size of characters	48 or 42 in font A, 64 or 56 in font B
Virtual printing	ESC/POS -OPOS- POS for .net compatibility



CONNECTORS

Interface	USB, RS232, Ethernet (optional Bluetooth interface)
Control of cash drawer	1 x RJ-11 6 pin dual port
Buzzer	Integrated
Power supply	AC100~220V (50~60HZ ≤ 1.5A)
Cables	USB, RS232 (included)
Drivers	Win 10/11/Linux/ Android SDK

PHYSICAL SPECIFICATIONS

Dimensions	175 x 144 x 130 mm
Weight	1.20 kg
Materials	Steel and ABS
Operating temperature	0 - 45°C, humidity of 10 - 80%
Storage temperature	-15°C / + 70°C
MCBF	100km of thermal paper, 1 million uses of the cutter
Colours	Black varnish and matt
Markings	CE, FCC, RoHS



Flash this code to check out the latest news on PERIMATIC