



SENOR X POS

Powerful fanless processor
in an ultra-slim design



The X POS system is a unique experience, both in terms of shape and technology. Its slim flat screen has been developed using “on Cell” technology, which means that the touch panel and LCD screen are one and the same. What’s more, the X touch terminal is presented on an elegant adjustable stand. Its discreet, stylish design in black and grey aluminium allow the system to be folded up and fully deployed in a totally ergonomic way.

The X POS terminal offers a wide range of options that integrate aesthetically and technologically with the top and bottom of the touch terminal, with no wires protruding from the installation.

As standard, it comes with an Intel® Core i3-1215U processor, a 256GB M.2 SSD (+ 1 available as an option) and an 8GB RAM memory, all covered by a tool-less cover. Data is transmitted via a single USB C cable, simplifying the connection system.

The X POS is the ideal design solution for optimising counter space.



PRODUCT KEY FEATURES

- Intel® Core i3-12th Fanless processor power
- Thinness and bright main screen
- Dedicated printer/scanner slot
- Wall-mounted POS

SYSTEM FEATURES

Processor	Intel® Core i3-1215U Dual Core 2.3GHz - fanless - 3M cache, 32- and 64-bit compatible
Memory	1 SO-DIMM 2400 MHz- DDR4 slot 8GB- Max. 16GB
Video	Intel® HD Graphics chipset
Audio	Realtek HD ALC259 card
Network	Integrated Realtek network card 10/100/1000
Data storage	1* SSD M.2 PCI Express 2280 - 256GB 1* SSD M.2 SATA available for storage expansion
Operating system	Windows 10, Linux
Manufacturer warranty	3 years

SCREEN SPECIFICATIONS

Display size	LCD 15.6" 16/9 - On cell technology. 16 mm
Luminance	300 cd/m ²
Resolution	1366 x 768 (16:9)
Touch-sensitive panel	Capacitive sensor technology

ACCESSIBLE CONNECTORS

I/O BOARD

USB	3 USB 2.0 ports, 1 USB 3.0 port
Series	2x RJ-48 -RS232 ports, adapters supplied
Network	1x RJ-45 port
Audio	1 mini HDMI input
Cash drawer	1 RJ11 rack output (24V)
Miscellaneous	2* built-in speakers

PHYSICAL SPECIFICATIONS

Dimensions	L.367 x D.195 x H.426-438
Weight	5 kg (in operation, without options)
Power supply	External integrated in stand / 19V DC - 110-240 VAC, consumption 60Watts max.
Materials	Aluminium, glass and ABS plastic
Temperature in operation	0C°/ + 40C°- Relative humidity 10%-90%
Storage temperature	-20C°/ + 60C°, Relative humidity 10%-90%
Colours	Grey - Alum
Cardboard box	57 x 56 x 17 (cm)

OPTIONS

Customer display module	XVFDI56, 2-line flat display unit 2x20 characters, internal USB link
Customer screen	XLCDI00, 11.6" LCD advertisement screen, 1024x768, internal USB link
Receipt printer	SGPR300L, Direct Thermal 260 mm/sec USB+LAN
Scanner	SGBS600M, omnidirectional USB scanner, 1D&2D
Integrated scanner	X2DI56, integrated 1D&2D scanner, QR code - PDF code, etc. right or left connection, 180° rotation



WALL-MOUNTED ABILITY




2D SCANNER

DEDICATED PRINTER/SCANNER AREA



INTEGRATED 2-LINE DISPLAY MODULE



Flash this code to check out the latest news on PERIMATIC