



O-LINK TOUCH POS PACK

A robust POS, integrated display and associated peripherals



Introducing the **O-Link** pack, the all-in-one solution in the SAGA range.

The POS is based on an Intel® Celeron 5205U processor combined with a projected capacitive technology touch panel and features a 2-line customer display integrated directly into the structure of the POS. The pack also includes a receipt printer and a wired 2D scanner.

The POS comes with 4GB of memory and data storage via a 128GB mSATA SSD hard drive.

The O-Link pack consists of the basic elements of a checkout station. The POS VESA 75 mount allows it to be installed on a mast to save counter space.



PRODUCT KEY FEATURES

- Reliable Intel® Celeron 5205U processor
- 15" LED screen with PCAP touch panel
- Easy cable routing in the stand with VESA75 mount
- Customer display integrated into the POS by default



SYSTEM CHARACTERISTICS

Processor	Intel Celeron 5205U Quad Core 1.8 GHz (max. 2.0 GHz)
Motherboard	Industrial type 170*170
Memory	4GB SO-DIMM, 2400 MHz as standard DDR4- Max 8GB
Video	Intel® HD Graphics chipset
Audio	Realtek HD Audio card
Network	Integrated network card 10/100 1x RJ45 + 1 mini PCI Express slot
Data storage	SSD M.2 128GB
Operating system	Windows 10 and Linux
Manufacturer warranty	3 years
Customer display module	Integrated 2-line x 20-character display module, with internal USB motherboard connection. Compatible with ESC/ POS and OPOS



INTEGRATED 2-LINE DISPLAY MODULE

SCREEN SPECIFICATIONS

Display size	LCD 15" (38 cm) LED, ratio 4: 3
Luminance	350 cd/m2
Resolution	XGA (1024 x 768)
Touch-sensitive panel	Capacitive sensor technology



CONNECTORS ON FRONT PANEL

USB	6 ports, including 4x 2.0 ports and 2x 3.0 ports
Series	2x RS-232 ports
Network	1x RJ-45 port
Miscellaneous	1 VGA port, 1 HDMI port, 1x 12V output
Audio	1 microphone jack input 1 jack line output



SGPR200II RECEIPT PRINTER

INCLUDED IN THE PACK

Printer	SGPR200II thermal receipt printer, 80 mm, 260 mm/sec, triple USB+RS-232 +LAN interface, USB and serial cables included
Paper	Paper roll of 80 mm thermal paper
Scanner	Wired hand-held scanner, 2D, USB connection, 1.50 metre cable + simplified programming manual
Options	Windows 10 Entry IOT Enterprise licence



SGBS-360 WIRED 2D SCANNER

PHYSICAL SPECIFICATIONS OF THE POS

Dimensions	L.350 x D.220 x H.310 (mm)
VESA attachment	Wall-mounted base and VESA75 mast-mounting option
Weight	3.8 kg
POS power supply	External / 12V DC - 5A - 260V 50-60GHz
Materials	Glass and ABS plastic
Temperature in operation	0C° / + 90C° non-condensing
Storage temperature	-40C° / + 75C°
Protection Index	IP 54 against splashes and dust
Colours	Black



Flash this code to check out the latest news on PERIMATIC