



O-LINK TOUCH POS PACK

A robust POS, integrated display and associated peripherals



Discover the **O-Link V2.0 pack**, an **all-in-one solution** from the SAGA range, with a modern and sleek design.

This point of sale terminal (POS) is equipped with an Intel® Celeron N5095 processor, **powering twice the performance** of the first version. Its projected capacitive touchscreen, combined with an LCD screen with 350 cd/m² brightness, ensures a great user experience.

The POS has a **built-in two-line customer display**.

The pack also includes a receipt printer and a wired 2D scanner, all packed in a shipping-friendly box – perfect for retailers.

With 4 GB of memory and a 128 GB mSata SSD, **easily accessible from the side**, the OL150V offers fast performance and reliable data storage. It's also **compatible with VESA 75/100 mounts**, allowing it to be installed on a pole to free up counter space.



PRODUCT KEY FEATURES

- Reliable Intel® Celeron 5095U processor
- 15" LED screen with PCAP touch panel
- Easy cable routing in the stand with VESA75 mount
- Customer display integrated into the POS by default

OL-150V

O-LINK PACK, ALL IN ONE

SYSTEM

CHARACTERISTICS

Processor	Intel Celeron 5095U Quad Core 1.8GHz (max 2.0 GHz)
Motherboard	Industrial type 170*170
Memory	4Go SO-DIMM, 2400 MHz as standard DDR4- Max 8Go
Video	Intel® HD Graphics chipset
Audio	Realtek HD Audio card
Network	Integrated network card 10/100 1xRJ45 + 1 mini PCI Express slot
Data storage	SSD M.2 128Go
Operating system	Windows 11 et Linux
Manufacturer warranty	3 years
Customer display module	Integrated 2-line x 20-character display module, with internal USB motherboard connection. Compatible with ESC/ POS and OPOS

SCREEN

SPECIFICATIONS

Display size	LCD 15" (38cm) LED, Ratio 4:3
Luminance	350 cd/m2
Resolution	XGA (1024 x 768)
Touch-sensitive panel	Capacitive sensor technology

CONNECTORS

ON FRONT PANEL

USB	8 ports, including 6x 2.0 and 2x 3.0 ports
Series	2 Port RS-232 ports
Network	1 port RJ-45 port
Miscellaneous	1 VGA port, 1 HDMI port, 1x 12V output
Audio	1 microphone jack input 1 jack line output

INCLUDE

IN THE PACK

Printer	SGPR200III thermal receipt printer, 80 mm, 260 mm/sec, triple USB+RS-232 +LAN interface, USB and serial cables included
Paper	Thermal Paper : 80x75 mm roll dimensions
Scanner	Wired hand-held scanner, 2D, USB connection, 1.50 metre cable + simplified programming manual
Options	Windows 11 Entry IOT Enterprise licence

PHYSICAL SPECIFICATIONS

OF THE POS

Dimensions	L.350 x P.220 x H. 310 (mm)
VESA attachment	Wall-mounted base and VESA75 mast-mounting option
Weight	3.8 kg
POS power supply	External / 12V DC - 5A - 260V 50-60GHz
Materials	Glass and ABS plastic
Temperature in operation	0C° / + 90C° non-condensing
Storage temperature	-40C° / + 75C°
Protection Index	IP 54 4 against splashes and dust
Colours	Black



INTEGRATED 2-LINE DISPLAY MODULE



SGPR200III RECEIPT PRINTER



SGBS-360 WIRED 2D SCANNER



SSD ACCESS ON THE SIDE



Flash this code to check out
the latest news on PERIMATIC