



K-320II

Fully autonomous ordering solution



Queue management, secure payment and customer autonomy are key issues for today's restaurants, fast food outlets, chain shops and leisure outlets (cinemas, museums, swimming pools, etc.). More and more retailers are starting to use customer checkout and ordering solutions:

Self-ordering.

That's why SAGA is offering a hardware solution: the KOBÉ 320 II touch-sensitive kiosk. It features all the basic elements of a stand-alone control station, including a 32" capacitive touchscreen, a thermal receipt printer and a 2D scanner, combined with a design that can accommodate an all-brand compatible payment terminal. What's more, the K320II self-ordering and payment kiosk has been designed for quick and easy access to the components (paper change, scanner settings, EPT connection, etc.) for immediate use.

It is available as a free-standing unit, however the self-service kiosk can be wall-mounted or supported by 2 modules (back-to-back) to increase sales space.



PRODUCT KEY FEATURES

- 32" self-ordering kiosk, Windows operating system
- Choice of stand or wall mounting and dual kiosks
- Integration of a 2D barcode reader
- Integration of a thermal receipt printer from the SAGA 80 mm range
- Default Wordline Valina EPT slot

CHASSIS

Materials	Steel, tempered glass, stainless steel
Dimensions with stand	L. 60 cm x D. 50 cm x H.(min) 187 cm, H.(max.) 207 cm
Trunk dimensions	L. 54.5 cm x D. 14 cm x H. 120 cm
Choice of mountings	Wall-mounted, free-standing or back-to-back
Weight	75 kg including stand

DISPLAY

Diagonal	32" TFT LCD (82 cm)
Resolution	1920 x 1080
MTBF	30,000 hours
Luminance	400 cd/m ²
Contrast Ratio	1200:1
Angle	H:178°, V:178°
Touch-sensitive panel	Projected capacitive 10 points
Coating	Anti-glare

PC CARD

Processor	Intel® Core i5-5250U, 2.4GHz
Chipset	Intel® HD Graphics
Memory	4GB, Max 8GB
Data storage	SSD 128GB
Connectors	6 USB ports 1 RJ45 port (LAN) 1 VGA input 3 COM ports, 2 of which are RJ45 1 microphone jack output
Wi-Fi	Wi-Fi card + integrated antennas

INTEGRATION

Thermal receipt printer	SGPR300L enclosed printer, USB+ LAN interface, 300 mm/sec print speed. Thermal coil 80 x 80 x12
Scanner	2D Barcode scanners, USB connection
EPT support	Valina Wordline compatible by default

OPTIONAL

Surveillance	Surveillance camera
Presence sensor	Customer presence detector integrated into front panel
Payment terminal	Mounts for EPTs Verifone, Atos, Hypercom, Pax, etc.
Inverter	3 connectors, 600 VA
Electrical connection	1.5 metre steel ceiling and wall connection tubes
Colours	Black



Flash this code to check out the latest news on PERIMATIC